Ecodora Srl
Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891 / +39 0424 571230
info@ecodora.com

P/N 0E3C1/5066VHHH

Diaphragm pump in aluminum with cataphoresis treatment series AAB-1-9 with multi ported inlet/outlet, membranes, balls and seats in Hytrel®



SECTORS OF USE

Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

FEATURES

Ratio	1:1
Flow rate	610 l/min
Max pressure	8 bar
Max cicles per minute	300 cpm
Delivery per cicles	0,590 l
Max suction lift	dry column 5 m - wet column 7,5 m
Max size pumpable solids	3 mm
Max working temperature	100 °C
Noise level	75 dB
Max air consumption	1,40 m^3/min
Air working pressure	2÷6 bar
Air inlet connection	G 3/8" (f)
Air outlet connection (muffler)	G 1/2" (f)
Fluid inlet connection	4 x G 1" (f)
Fluid outlet connection	5 x G 1" (f)
Balls for inlet	ball valve
Membranes	Hytrel®

Balls	Hytrel®
Seats	Hytrel®
Packing	No. 1 - 0,03 m³
Gross weight	13 kg