

## P/N 0E3C3/2666VTTP



Diaphragm pump in aluminum with cataphoresis treatment series AAB-114 with membranes and balls in Teflon® and seats in polypropylene

### SECTORS OF USE

Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

### FEATURES

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Ratio                           | 1:1                               |
| Flow rate                       | 150 l/min                         |
| Max pressure                    | 8 bar                             |
| Max cycles per minute           | 260 cpm                           |
| Delivery per cycles             | 0,800 l                           |
| Max suction lift                | dry column 5 m - wet column 7,5 m |
| Max size pumpable solids        | 3 mm                              |
| Max working temperature         | 100 °C                            |
| Noise level                     | 75 dB                             |
| Max air consumption             | 1,80 m³/min                       |
| Air working pressure            | 2÷6 bar                           |
| Air inlet connection            | G 3/4" (f)                        |
| Air outlet connection (muffler) | G 1" (f)                          |
| Fluid inlet connection          | G 1.1/4" (f)                      |
| Fluid outlet connection         | G 1.1/4" (f)                      |
| Balls for inlet                 | ball valve                        |



|              |                 |
|--------------|-----------------|
| Membranes    | PTFE+Hytrel®    |
| Balls        | PTFE            |
| Seats        | polypropylene   |
| Packing      | No. 1 - 0,03 m³ |
| Gross weight | 15 kg           |