Ecodora Srl
Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891 / +39 0424 571230
info@ecodora.com

P/N 0E3C6/50111TTP

Diaphragm pump in aluminum series AABM-2 modular with 2" flanges, membranes and balls in Teflon® and seats in polypropylene

SECTORS OF USE


Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

FEATURES

Ratio	1:1
Flow rate	550 l/min
Max pressure	8 bar
Max cicles per minute	147 cpm
Delivery per cicles	3,950 l
Max suction lift	dry column 5 m - wet column 7,5 m
Max size pumpable solids	6,5 mm
Max working temperature	100 °C
Noise level	82 dB
Max air consumption	4 m³/min
Air working pressure	2÷6 bar
Air inlet connection	G 3/4" (f)
Air outlet connection (muffler)	G 1" (f)
Fluid inlet connection	ANSI 150 - DIN PN 10 - JIS 10K 2" (50 mm)



OVERALL DIMENSIONS (mm)



Fluid outlet connection	ANSI 150 - DIN PN 10 - JIS 10K 2" (50 mm)
Balls for inlet	ball valve
Membranes	Teflon®+Hytrel®
Balls	Teflon®
Seats	polypropylene
Packing	No. 1 - 0,130 m³
Gross weight	50 kg