Ecodora Srl
Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891 / +39 0424 571230
info@ecodora.com

P/N 0E33500



Diaphragm pump series AB-34 in aluminum for water, mineral-vegetable oils and diesel fuel. R. 1:1 - 70 l/min with membranes in NBR, balls in Hytrel® and rigid suction tube for drums 180÷220 kg

SECTORS OF USE

Agriculture, Automotive, Building and road construction, Lube trucks and transports

FEATURES

Ratio	1:1
Flow rate	70 l/min
Compatible fluids	water, mineral-vegetable oils, diesel fuel
Pump material	aluminum
Ball valve material	Hytrel®
Air inlet connection	G 3/8" (f)
Fluid inlet-outlet connection	suction tube ø 34 mm - G 3/4" (f)
Air working pressure	2÷6 bar
Max supply pressure	8 bar
Average air consumption	500 l/min
Noise level	75 dB
Fluid temperature	-10÷+65 °C
Max solids diameter	ø 1,5 mm
Suitable for drums or tank	suitable for drums 180÷220 kg
Suction-delivery ball valve with spring	ball valve with spring

Packing	No. 2 - 0,040 m³
Weight	10 kg