**Ecodora Srl**
Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891 / +39 0424 571230
info@ecodora.com

# P/N 0E63095

Pneumatic piston pump s. 700, R 65:1 - 1900 g/min, with PU seals and suction tube 940 mm



## SECTORS OF USE

Agriculture, Automotive, Building and road construction, Lube trucks and transports

## FEATURES

| | |
|---|---|
| Ratio | 65:1 |
| Flow rate | 1900 g/min |
| Compatible fluids | greases medium/high viscosity |
| Suction tube upper body | aluminum |
| Suction tube | carbon steel |
| Air inlet connection | G 1/4" (f) |
| Fluid outlet connection | G 3/8" (f) |
| Air working pressure | 6÷8 bar |
| Average air consumption | 440 l/min |
| Noise level | 81 dB |
| Air max pressure | 8 bar |
| Suitable for drums | 180÷220 kg |
| Pump | - |
| Hose reel | - |
| Gun | - |
| Drum cover | - |
| Follower plate | - |
| Grease connection hose | - |

| | |
|---|---|
| Nipple | - |
| Drip-tray | - |
| Packing | No. 1 - 0,020 m³ |
| Weight | 8,2 kg |