**Ecodora Srl**
Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891 / +39 0424 571230
info@ecodora.com

# P/N 0E33396

AISI 304 stainless steel pneumatic piston pump s. 600, R 1:1 - 30 l/min, with Viton® seals and suction tube 940 mm. Suitable for 180÷220 kg drums



## SECTORS OF USE

Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

## FEATURES

| | |
|---|---|
| Ratio | 1:1 |
| Flow rate | 30 l/min |
| Compatible fluids | suitable for antifreeze and windshield washing liquid |
| Suction tube upper body | AISI 304 stainless steel |
| Suction tube | AISI 304 stainless steel |
| Air inlet connection | G 1/4" (f) |
| Fluid outlet connection | G 1/2" (f) |
| Air working pressure | 6÷8 bar |
| Average air consumption | 370 l/min |
| Noise level | 81 dB |
| Max deliverable oil viscosity | 50 SAE |
| Bung adaptor | standard |
| Suitable for drums or tanks | suitable for drums 180÷220 kg |
| Packing | No. 1 - 0,02 m³ |
| Weight | 7,4 kg |