**Ecodora Srl**
Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891 / +39 0424 571230
info@ecodora.com

# P/N 0E3325F

Cable reel s. 280, supply voltage 230 V single phase, without socket. Number of conductors 3, cable type 3G x 2,5 - H07 RN-F, cable length 7 + 1 (m). Rewinding clutch as standard

## SECTORS OF USE

Agriculture, Automotive, Cleaning, Building and road construction, Industry, Mining, Lube trucks and transports

## FEATURES

| | |
|---|---|
| Information | 230 V single phase |
| Protection degree of electrical part | IP44 |
| Environment temperature | -5÷+40 °C |
| Number of conductors | 3 |
| Cable type | 3Gx2,5 - H07 RN-F |
| Cable length | 7+1 m |
| Cable inlet | 1,2 m |
| Max power use (20 °C) wound | 1,9 kW |
| Max power use (20 °C) unwound | 3,5 kW |
| Thermal protector | yes |
| Rewinding clutch | yes |
| Socket | - |
| Plug | - |
| Packing | No. 1 - 0,043 m³ |
| Gross weight | 6,4 ÷ 8,2 kg |




## OVERALL DIMENSIONS (mm)

