

## P/N 0E4510F

Cable reel s. 280, supply voltage 400 V three phase.  
Number of conductors 5, cable type 5G x 1 - H05 VV-F,  
cable length 11 + 1 (m). Rewinding clutch as standard

### SECTORS OF USE

Agriculture, Automotive, Cleaning, Building and road  
construction, Industry, Mining, Lube trucks and  
transports

### FEATURES

|                                      |                              |
|--------------------------------------|------------------------------|
| Information                          | 400 V three phase            |
| Protection degree of electrical part | IP44                         |
| Environment temperature              | -5 ÷ +40 °C                  |
| Number of conductors                 | 5                            |
| Cable type                           | 5Gx1 - H05 VV-F              |
| Cable length                         | 11+1 m                       |
| Cable inlet                          | 1,2 m                        |
| Max power use (20 °C) wound          | 1 kW                         |
| Max power use (20 °C) unwound        | 2,3 kW                       |
| Thermal protector                    | yes                          |
| Rewinding clutch                     | yes                          |
| Socket                               | -                            |
| Plug                                 | -                            |
| Packing                              | No. 1 - 0,043 m <sup>3</sup> |
| Gross weight                         | 6,4 ÷ 8,2 kg                 |



### OVERALL DIMENSIONS (mm)

