

## P/N OE871602/2000

Hose reel with electric motorization 400 V AC - 50/60 Hz in painted steel, ATEX s. 700, for air-water and diesel, 20 bar, without hose. Drum width 690 mm. Inlet-outlet G 2" (f)

### SECTORS OF USE

Industry, Mining, Lube trucks and transports

### FEATURES

|                   |                                      |
|-------------------|--------------------------------------|
| Pressure          | 20 bar                               |
| Compatible fluids | air - water - diesel fuel            |
| Swivel joint      | aluminum                             |
| Seals             | Viton®                               |
| Characteristic    | electric 400 V AC - 50/60 Hz<br>ATEX |
| Material          | painted steel                        |
| Couplings         | -                                    |
| Hose              | -                                    |
| ø e hose length   | -                                    |
| Inlet             | G 2" (f)                             |
| Outlet            | G 2" (f)                             |
| Reel flow path    | aluminum - zinc plated steel         |



### FURTHER FEATURES

| Capacity 3/8" | Capacity 1/2" | Capacity 3/4" | Capacity 1" | Capacity 1.1/4" | Capacity 1.1/2" | Capacity 2" |
|---------------|---------------|---------------|-------------|-----------------|-----------------|-------------|
| 550 m         | 350 m         | 244 m         | 134 m       | 84 m            | 75 m            | 43 m        |