

Via Marangoni 33, 36022 S. Zeno di Cassola (VI) Italy Tel. +39 0424 570891 info@ecodora.com

P/N 4456/11



Enclosed fixed hose reel in ABS with brackets in painted steel, s. 430, for air-water-antifreeze, 20 bar, black synthetic hose 15 m, ø 1/2". Cental pin in AISI 304 stainless steel

SECTORS OF USE

Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

FEATURES

Pressure 20 bar Compatible fluids air-water-antifreeze Swivel joint brass Seals Viton® Characteristic fixed Material painted steel with ABS drum Couplings zinc plated steel Hose p/n 962/15		
Swivel joint brass Seals Viton® Characteristic fixed Material painted steel with ABS drum Couplings zinc plated steel	Pressure	20 bar
Seals Viton® Characteristic fixed Material painted steel with ABS drum Couplings zinc plated steel	Compatible fluids	air-water-antifreeze
Characteristic fixed Material painted steel with ABS drum Couplings zinc plated steel	Swivel joint	brass
Material painted steel with ABS drum Couplings zinc plated steel	Seals	Viton [®]
Couplings zinc plated steel	Characteristic	fixed
	Material	painted steel with ABS drum
Hose p/n 962/15	Couplings	zinc plated steel
	Hose	p/n 962/15
ø e hose length ø 1/2" - 15 m	ø e hose length	ø 1/2" - 15 m
Inlet G 1/2" (m)	Inlet	G 1/2" (m)
Outlet G 1/2" (f)	Outlet	G 1/2" (f)
Reel flow path brass, AISI 304 stainless steel and zinc plated steel	Reel flow path	



OVERALL DIMENSIONS (mm)

