

P/N 0E3C3/5066VHHH



Diaphragm pump in aluminum with cataphoresis treatment series AAB-2 with multi ported inlet/outlet, membranes, balls and seats in Hytrel®

SECTORS OF USE

Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

FEATURES

| | |
|---------------------------------|--------------------------------------|
| Ratio | 1:1 |
| Flow rate | 610 l/min |
| Max pressure | 8 bar |
| Max cycles per minute | 147 cpm |
| Delivery per cycles | 4,150 l |
| Max suction lift | dry column 5 m - wet column 7,5 m |
| Max size pumpable solids | 6,5 mm |
| Max working temperature | 100 °C |
| Noise level | 82 dB |
| Max air consumption | 4,00 m ³ /min |
| Air working pressure | 2÷6 bar |
| Air inlet connection | G 3/4" (f) |
| Air outlet connection (muffler) | G 1" (f) |
| Fluid inlet connection | G 2.1/2" (f) |
| Fluid outlet connection | G 2" (f) |
| Balls for inlet | ball valve |
| Membranes | Hytrel® |



| | |
|--------------|-----------------------------|
| Balls | Hytrel® |
| Seats | Hytrel® |
| Packing | No. 1 - 0,12 m ³ |
| Gross weight | 45 kg |