

**P/N  
0E3C6/5066VTTP**

Diaphragm pump in aluminum with cataphoresis treatment series AABM-2 modular with 2" flanges, membranes and balls in Teflon® and seats in polypropylene

**SECTORS OF USE**

Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

**FEATURES**

Ratio	1:1
Flow rate	550 l/min
Max pressure	8 bar
Max cycles per minute	147 cpm
Delivery per cycles	3,950 l
Max suction lift	dry column 5 m - wet column 7,5 m
Max size pumpable solids	6,5 mm
Max working temperature	65 °C
Noise level	82 dB
Max air consumption	4,00 m <sup>3</sup> /min
Air working pressure	2÷6 bar
Air inlet connection	G 3/4" (f)
Air outlet connection (muffler)	G 1" (f)
Fluid inlet connection	ANSI 150 - DIN PN 10 - JIS 10K 2" (50 mm)



Fluid outlet connection	ANSI 150 - DIN PN 10 - JIS 10K 2" (50 mm)
Balls for inlet	ball valve
Membranes	PTFE+Hytrel®
Balls	PTFE
Seats	polypropylene
Packing	No. 1 - 0,13 m <sup>3</sup>
Gross weight	50 kg