**Ecodora Srl**
Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891 / +39 0424 571230
info@ecodora.com

# P/N 0E33/3011NHHV2

Diaphragm pump in aluminum series AB-114 with membranes in NBR, balls and seats in Hytrel®



## SECTORS OF USE

Agriculture, Automotive, Building and road construction, Lube trucks and transports

## FEATURES

| | |
|---|---|
| Ratio | 1:1 |
| Flow rate | 200 l/min |
| Compatible fluids | water, mineral-vegetable oils, diesel fuel |
| Pump material | aluminum |
| Ball valve material | Hytrel® |
| Air inlet connection | G 3/4" (f) |
| Fluid inlet-outlet connection | G 1.1/4" (f) x G 1.1/4" (f) |
| Air working pressure | 2÷6 bar |
| Max supply pressure | 8 bar |
| Average air consumption | 1400 l/min |
| Noise level | 75 dB |
| Fluid temperature | -10÷+90 °C |
| Max solids diameter | ø 3 mm |
| Suitable for drums or tank | - |
| Suction-delivery ball valve with spring | ball valve with spring |
| Packing | No. 1 - 0,041 m³ |

| | |
|---|---|
| Weight | 16 kg |